


Common reference frame for sea and land – challenges and recommendations

Aksel Voldsund, NSHC-TWG
05.02.2020




Project objective

- Determine the relationship between the height datum on land and the Chart Datum, using the ellipsoid as a common reference
- Develop guidelines for a method that can be used along the entire Norwegian coast
- Collaboration between the Hydrographic Service and the Geodetic Institute within the Norwegian Mapping Authority



Surfaces and models involved



(1) = Mean Dynamic Topography (MDT) model

(2) = Z0-model

(3) = Quasi Geoid model

(4) = Mean sea level model

Challenging topography

- Rough topography
- High mountains
- Deep fjords
- Complex coastline




Study areas

First phase (2015-2017)

- Many types of measurements



Fieldwork phase 1



Study areas

First phase (2015-2017)

- All measurements into a collocation «engine»
- The requested models were calculated
- ...but...



Study areas

First phase (2015-2017)

- All measurements into a collocation «engine»
- The requested models were calculated
- ...but...
- Gradients in MDT hardly significant
- The focus area might be too kind



Phase 2

- Check the method in an area where changes in the MDT was expected to be more significant
- Hydrodynamic modelling to investigate spatial variations in the MDT
- Use satellite altimetry to close the gap between the MSS carried out in the coastal zone and the altimetry derived MSS for the open ocean

Study areas

Second phase:
2018-19

Study in the
Sognefjord



The Sognefjord

- 204 km long
- East-West (across the coastline)
- 1300 m deep
- Surrounded by 1700 m high mountains
- 1-2 km broad at its most narrow




Field work and measurements

- Temporary tide gauges
- Levelling campaigns
- GNSS measurements
- Altimetry data
- Hydrodynamical models




Water level measurements (phase 1 and 2)


- All measurements are used to make models for the entire area
- The tide gauges in the Sognefjord have been collecting data for more than a year
- 6 of the gauges are still collecting data



Average water level




Tilting Sea Surface




Period of observations to reach a standard deviation of 1 cm

Mean Sea Level transferred from Bergen




GNSS/levelling points

- Mainly levelled points in the national network
- Some are levelling benchmarks measured in a five days GNSS campaign




How to calculate the models?


- ↔ GNSS/levelling point
- ↔ Temporary tide gauge connected with levelling
- ↔ Temporary tide gauge NOT connected with levelling




Calculation strategy




Mean Dynamic Topography




Quasi geoid-model



Z0-model – the amplitude of the tides



Z0-calculations and seasonal variations



Test of Hydrodynamical models


- Three different runs from two different models were tested
- Aim was:
 - To connect the average water level from short time series to MSL
 - To reduce the need for water level measurements
 - To find the MDT directly by averaging the model output over 19 years

Test of Hydrodynamical models

- Never before validated against water level observations
- None of the models were able to give realistic results inside the fjords
- Some issues related to resolution, tidal forcing, storm surge and inverse barometric corrections
- Comparison of MDT from the models and the permanent tide gauges at the coast show promising results
- Feedback is given to the owners of the models. Assume that models will be usefull in making MDT-models in the near future

Satellite Altimetry

Comparison with the altimetry model NMBU18MDT



Conclusions

- The variations in the MDT are much smaller and have longer wavelengths than variations in the Quasi geoid
- Water level observations could contribute to improve the Quasi geoid at large distances from the levelling network
- There are challenges related to transferring information from the permanent tide gauges to the temporal tide gauges
- At the time being, hydrodynamic models are not suitable for calculating the MDT inside fjords, but we are optimistic regarding the future
- Satellite altimetry has its primary strengths off shore, but this might change in the near future

Recommendations

- Start by calculating separation models covering the entire Norwegian coast based on existing data, and update these models continuously as more data is collected
- Continue improving the source data by measuring the water level, and carry out GNSS and levelling campaigns
- Increase the density of the permanent tide gauge network to minimize errors associated with transferring information from long to short time series

Recommendations

- Follow the development regarding satellite altimetry and hydrodynamical models
- Start the work where the need for information is largest
- Just get started!